

HDA Metal Lined Slurry Pumps (Equal with Warman AH pumps)



Usage: Slurry, Sewage and sludge water

Technical Data:

Capacity: 13-5000m³/h

Head: 6-120 m

Size : 1-20 inch

Material: Hard Chrome Alloy(A05,A07,A51,A61,etc.)

Drive: Diesel or Electric

HDR Rubber Lined Slurry Pumps (Equal with Warman AHR pumps)



Usage: Slurry, Sewage and Sludge water

Technical Data:

Capacity: 3-2500m³/hr (1000 l/s)

Head: 3-91m

Size : 1-20 inch

Material: Rubber(R55),PU,EPDM,Butyl,SO2,etc.

Drive:: Diesel or Electric

HDL Light Duty Slurry Pumps (Equal with Warman L pumps)



Usage: Slurry, Sewage and water

Technical Data:

Capacity: 2-3320m³/h

Head: 3-59m

Size : 1-12 inch

Material: Hard Chrome Alloy(A05,A07,A51,A61,etc.)

Drive: Diesel or Electric

HDH High Pressure slurry pumps (Equal with Warman HH pumps)



Usage: Slurry, Sewage and water

Technical Data:

Capacity: 16-1008m³/h

Head: 25-118m

Size : 1-6 inch

Material: Hard Chrome Alloy(A05,A07,A51,A61,etc.)

Drive: Diesel or Electric

Shijiazhuang Hedun Pump Co.,Ltd.

HDG Gravel pump(Equal with Warman G pumps)



Usage:Slurry,Sand,Sewage and sludge water

Technical Data:

Capacity: 60-10000m³/h

Head: 5-70 m

Size : 4-18 inch

Material: Cr Alloy(A05,A07,etc)

Drive: Diesel or Electric

HDZJ Slurry pumps



Usage:Slurry, Sand dredging,Sewage and sludge water

Technical Data:

Capacity: 4-1830m³/h

Head: 7-133 m

Size : 1.6-12 inch

Material: Hard Chrome Alloy(A05,A07,A51,A61,etc.)

Drive: Diesel or Electric

HDZGB Slurry pumps



Usage:Slurry,Sand,Sewage and sludge water

Technical Data:

Capacity: 10-533m³/h

Head: 25-95 m

Size : 2.6-12 inch

Material: Hard Chrome Alloy(A05,A07,A51,A61,etc.)

Drive Diesel or Electric

HDV(R) Sump Slurry Pumps(Equal with Warman SP/SPR Sump pumps)



Usage:Slurry, Sand,Sewage and sludge water

Technical Data:

Capacity: 19-1267m³/h

Head: 4-40 m

Size : 1.6-12 inch

Material: Hard Chrome Alloy or Natural Rubber

Drive Electric

ZJQ Submersible slurry pump



Usage:Slurry, Sand dredging,Sewage and sludge water

Technical Data:

Capacity: 30~1450 m³/h

Head: 15~95 m

Size : 2-8 inch

Material: Hard Chrome Alloy A05

Drive Electric

Shijiazhuang Hedun Pump Co.,Ltd.

FDG Desulphurization pumps(Equal with Warman TL pumps)



Usage: flue gas for power plant
Technical Data:

Capacity: 2.5-10440 m³/h
Head: 10-92 m
Size : 1-40 inch
Material: Hard Chrome Alloy A49,Ceramic
Drive Electric

Single casing Desulphurization pumps



Usage: flue gas for power plant
Technical Data:

Capacity: 27-14076 m³/h
Head: 5-150 m
Size : 2-36 inch
Material: Hard Chrome Alloy A49,Ceramic
Drive Electric

WN Deredger Pumps



Usage: Marine dredging for dredger with large capacity
Technical Data:

Capacity: 600~25000 m³/h
Head: 20-76 m
Size : 8-40 inch
Material: Hard Chrome Alloy A05
Drive: Electric

Vertical Froth Pumps (Equal with Warman AF froth pumps)



Usage: froth slurry
Technical Data:

Capacity: 6-575 m³/h
Head: 5-30 m
Size : 2-8 inch
Material: Hard Chrome Alloy A05
Drive: Electric

Horizontal Froth Pumps (Equal with Warman AHF froth pumps)



Usage: froth slurry

Capacity: 30~1450 m³/h
Head: 15~95 m
Size : 2-8 inch
Material: Hard Chrome Alloy A05
Drive: Electric

Handled liquids : Mining Dewatering, Ore slurry, Ash, Iron, Bauxite, Bronze, Sand Sludge, etc...

Applications : Power plant, Coal washing, Sand dredging, Chemical industry, Mining, Cement, Steel plants...

Different material Options	Wet part Material Options	Hard Chrome Alloy(A05, A07, A49, A51, A33, A61)
		Natural Rubber
		S01, S12, S21, S42, S50, U01, EPDM, Butyl, PU
		Ceramic
	Bearings	Heavy duty bearings and Original Bearings
	Shaft Sleeves	3Cr13, 4Cr13, SS304, SS316
	Bearing housing	G01, D21
	Shaft	45#, 40Cr, SS304, SS315...
	Lantern Ring	304, 316, PTFE, Cu
	Sealing	Stainless Steel mechanical seals
	Hi-seal	
	PTFE Packing	

Hedun pump spare parts



Chrome alloy metal

Abrasive rubber

Ceramic

